SNAP-ON ASIA MANUFACTURING

FEATURES & SPECIFICATIONS



In Snap-on, we provide world class quality product with excellence in design and manufacturing





CNC lazer cutting provide precise cutting and efficient process



Robotic welding - High productivity, less downtime and consistent quality



State of the art pre-treatment provide uniform coating and excellent corrosion protection



Organized, clean and systematic work environment to ensure safety and high quality control

	3.5 Ton Clear Floor	4 Ton Floor Plate	4 Ton Clear Floor
Capacity	3.5 Ton	4 Ton	4 Ton
Overall Width	3402 mm	3402 mm	3397/3647 mm
Width between Column	2752 mm	2752 mm	2747 / 2997 mm
Drive-thru	2437 mm	2437 mm	2415 / 2665 mm
Overall Height	3705 mm	2821 mm	3515 / 3815 mm
Under Bar Clearance	3593 mm	NA	3403.5 / 3703.5 mm
Lifting Pad	114-159 mm	114-149 mm	128-173 mm
Front Arm	2 Stage (802-1202 mm)		3 Stage (720-1320 mm)
Rear Arm	2 Stage (802-1202mm)		3 Stage (720-1320 mm)
Design	Symmetrical		
Secondary Lock	Dual Point Mechanical		

SINGAPORE

Snap-on Tools Singapore Pte Ltd 25 Tagore Lane, #01-02, Singapore 787602 Tel: (65) 6451-5570 • Fax: (65) 6451-5574

INDONESIA

Snap-on Tools Singapore Pte Ltd - Indonesia Rep. Office Graha Pratama Building, 20th Floor JI. M.T. Haryono Kav 15, Jakarta 12810, Indonesia Tel: (62-21) 8370-9611 • Fax: (62-21) 8370-9612

MALAYSIA

Snap-on Tools Singapore Pte Ltd - Malaysia Branch Unit A-2-3, Block A, 3-2, Jaya One No. 72A, Jalan Universiti 46200 P.J., Selangor, Malaysia Tel: (603) 7957-3088 • Fax: (603) 7958-2088

PHILIPPINES

Snap-on Tools Singapore Pte Ltd - Philippines Branch 4/F, 2053 Building, Edison Street, San Isidro Makati City, 1234 Philippines Tel: (63-2) 843-7935 • Fax: (63-2) 843-7730

> John Bean is committed to product innovation and improvement. Therefore, specifications listed in this brochure may change without notice. © 2013 Snap-on Incorporated. John Bean is a trademark, registered in the United states and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 12/13 25121401J

TWO POST AUTOMOTIVE LIFTS

3.5 Ton Clear Floor 4 Ton Clear Floor 4 Ton Floor Plate

TAIWAN

Snap-on Tools Singapore Pte Ltd - Taiwan Branch 3F-4, #9 Wuquan 1st Road, New Taipei Industrial Park, Xinzhuang District 24892, New Taipei City, Taiwan ROC Tel: (886-2) 2298-9789 • Fax: (886-2) 2298-2288

HONG KONG

Snap-on Tools Hong Kong Limited Unit 2010, 20/F, Laford Centre, 838 Lai Chi Kok Road Cheung Sha Wan, Kowloon, Hong Kong Tel: (852) 2370-3700 • Fax: (852) 2370-3400

KOREA

Snap-on Tools Korea #505 & 506, BuCheon Techno Park Block 3, Building 301, 365 SamJung-Dong, OhJung-Gu Bucheon City, GyeongGi-do, Korea 421-809 Tel: (82-32) 326-7310 • Fax: (82-32) 326-7312

THAILAND

Snap-on Tools (Thailand) Co. Ltd. 5th Floor, Talomsim Building, 924 Rama 3 Road Bangpongpang Yannawa, Bangkok 10120, Thailand Tel: (66) 2294-9660 • Fax: (66) 2294-9665









3.5 TON CLEAR FLOOR

4 TON CLEAR FLOOR 4 TON FLOOR PLATE




- Designed for car and light trucks up to 3.5 Ton
- Semi-symmetric: Large swing arm area designed to cater for various lifting position
- Secure: Rubber doors guard prevent damages when moving in/out of the vehicle. Heavy duty arm restrains and hydraulic hose guards designed to be safe and long lasting.
- Smooth lift operation: Nylon glide blocks are used to provide durable and smooth lift operation
- Arm pads: Adjustable screw with stackable rubber lifting pad



Safety shut-off bar



Heavy duty arm restraints



Electro-hydraulic chain over system

Best in class design of uncompromising quality and safety

4 TON FLOOR PLATE

Floor Plate

• 2821 mm overall column height is an ideal solution for low ceiling workshop

System

 Heavy duty chain over electric hydraulic lifting with cable equalization

Safety

• Heavy duty column with symmetrical 2-stage front and rear arm

TWO POST AUTOMOTIVE LIFTS

4 TON CLEAR FLOOR

Overall Height: 3515 / 3815 mm Overall Width: 3397 / 3647 mm

Flexibility

 Adjustable height and width options to accommodate vary service bay sizes

Safety

- Padded overhead shut-off bar and large rubber door guards prevent damages
- Thicker pulley cables and steel pulleys for improved durability


Surface


 Premium power coat finish provide long lasting durability

Arm


- Long reaching three stage front and rear arms 720 mm to 1320 mm
- It also comes with adjustable rubber screw pads inserts

Standard 3-Stage arm enable symmetric and asymmetric lifting capabilities





2-Stage for 3.5 Ton **Clear Floor / 4 Ton** Floor Plate



3-Stage arm for 4 Ton **Clear Floor**



Aluminium Housing **Power Pack** (Optional)

Available in: 1) 3PH, 38oV (50 Hz) 2) 1PH, 220V (50/60 Hz)



Heavy Duty Height Adaptor (Optional)



John Bean manufactures a complete line of **Automotive Wheel Service Equipment**



Wheel Balancer



Tire Changer



Wheel Aligner



